

# Lusin<sup>®</sup> Clean Granulati za čišćenje

Lusin<sup>®</sup> Clean tehnologija pruža idealne čistače, koji ne ispuštaju dim i neprijatan miris, a namijenjeni su za mašine za injekciono presovanje i ekstrudere. Granulatna forma čistača ne sadrži abrazive i omogućava brzo, efektivno čišćenje mašina za injekciono presovanje i malu potrošnju materijala.

Od granulata za čišćenje, sredstava protiv korozije, čistača alata, preko maziva i sredstava za odvajanje, očekujte najbolje.

Posetite nas na:

[www.chemtrend.com](http://www.chemtrend.com)

 **Chem  
Trend**

*Release Innovation<sup>™</sup>*

# Lusin<sup>®</sup> Clean

## Granulati za čišćenje



Lusin <sup>®</sup> Granulati za čišćenje		Injection Molding	Blow Molding	Extrusion (Film)	Extrusion (Sheet, Profile, Pipe, Wire & Cable)	Compounding	Pass filter	Hot runner suitable	NSF registered	Polyolefins	PS	SAN, ABS, ASA	PVC	PTFE, PVDF	PMMA	POM	PA6, PA66, PA610, PA11, PA12	PC, PC/ABS	PET, PBT	PP0, PEEK, PPS, PES, PSU, LCP	CA, CAB, CP	TPU, TPE	Temperature range > 300 °C/572 °F	Temperature range 180-300 °C/356-572 °F	Temperature range 120-250 °C/248-482 °F
Proizvod	Oblik																								
Lusin <sup>®</sup> Clean G 320	Granule	●				◐	●	●	●	◐	●	●	◐	●	●	●	●	○	●		●	◐	○	●	
Lusin <sup>®</sup> Clean G 315	Granule	●			●	●	●	●	●		○	○	◐	○	◐		●	◐				◐	○	●	
Lusin <sup>®</sup> Clean OH 311	Granule	●			●	●	●	●		◐	○	○	●		◐	◐	●					●	○	●	◐
Lusin <sup>®</sup> Clean OH 251	Granule	●			●	●	●	●		◐			●			◐	◐					●		●	◐
Lusin <sup>®</sup> Clean G 410	Granule	●				○	●	●	●											●			●	●	
Lusin <sup>®</sup> Clean 1500 <sup>1</sup>	Granule	●				●	●	●							○		◐	●	◐				◐	●	
Lusin <sup>®</sup> Clean G 295 C <sup>2</sup>	Granule	●					●	●	●			●					◐	◐					◐	●	
Lusin <sup>®</sup> Clean G 300	Granule	◐	●		●		●	●	●		●	●	●		●	●	●	◐	●	●			●	●	
Lusin <sup>®</sup> Clean G 301	Granule	◐	●		●		●	●	●									◐	●	●			●	●	
Lusin <sup>®</sup> Clean LD 250	Granule	◐*		●	◐		●	●	●	●			●				◐								●

U slučaju prelaska sa materijala A na materijal B, čistiti se Lusin<sup>®</sup> granulatom koji se slaže sa materijalom A

<sup>1</sup> koncentrat (25% Lusin<sup>®</sup> Clean 1500/ 75% osnovnog materijala)

<sup>2</sup> koncentrat (30% Lusin<sup>®</sup> Clean G 295C/ 70% osnovnog materijala)

\* Zatvarači i poklopci

● veoma preporučljivo/da

◐ srednje preporučljivo

○ ne preporučuje se